

VISTA-50P VISTA-50PUL



With its powerful performance and reliability, the VISTA-50P is the solution for all your installation needs.

Meets UL Commercial Burglary requirements when using the VISTA-50PUL

The VISTA-50P is a superior control panel that provides flexibility of up to eight independent partitions with the economy of a single control.

FEATURES

- ◆ Nine hardwired zones standard
- ◆ Eight partitions standard
- ◆ 75 user codes work in all partitions
- ◆ Seven authority levels
- ◆ 5800 wireless compatibility
- ◆ Supports two-wire multiplex
- ◆ 87 total zones
- ◆ 224 event memory log/printer option
- ◆ Scheduling of events (real time clock)
- ◆ Keypad macro features
- ◆ Master console option for viewing all partitions at a glance
- ◆ Common lobby logic
- ◆ Fast downloading
- ◆ Supports up to 16 relays and/or X-10
- ◆ Quick start programming
- ◆ False alarm features
- ◆ UL Commercial Burg Listed when using the VISTA-50PUL

APPLICATION OPTIONS

- ◆ Wireless remote control - single button system operation:
 - 5804 - a four button programmable wireless key
 - 5804BD - a bi-directional button programmable wireless key with system status feedback
- ◆ Single or dual button wireless personal panic:
 - 5802MN - 5802MN2
- ◆ Home control features that activate lights, appliances, garage doors, and numerous other devices
- ◆ Vista Interactive Phone Module (VIP) that gives the end user control of their system from any touch tone phone. The 4285 VIP responds in English, with a vocabulary of over 100 words
- ◆ Full English display keypads for clear understanding of system status and zone locations
- ◆ Time event applications:
 - Open garage doors and turn on the lights
 - Provides that "lived in look" while away from home
 - Ability to limit access to parts of the home at certain times

VISTA-50P VISTA-50PUL

SPECIFICATIONS:

ELECTRICAL:

- ◆ Aux power 12 VDC, 750mA max
- ◆ 16.5 VAC/40 VA transformer
- ◆ Alarm output 12 VDC, 2.8 Amps max
- ◆ For UL installations, combined Aux and alarm output cannot exceed 750mA

OUTPUT CONTROL:

- ◆ Supports up to four relay boards (part no. 4204)
- ◆ Supports four relays for a total of 16
- ◆ Optional X-10 transformer/interface (part no. 4300) maybe used to control X-10 receiving devices
- ◆ Each X-10 receiver address counts as one relay when computing total relays
- ◆ Real time clock can be used for relay/X-10 control

ZONES:

- ◆ Eight hardwired zones
 - Selectable response: 10msec, 350msec, 750msec
 - Assignable to any partition
 - 16 zone types to choose from
 - Programmable swinger suppression

SUPPORTED DEVICES

Hardwired Expansion Devices:

- ◆ 4208 eight zone expansion module
- ◆ Powerline support - 4300 transformer/interface
- ◆ Keypads
 - 6139 custom English (required for programming) -100mA
 - 6128 fixed English LCD-85mA/40mA
- ◆ Voice module 4285 VIP-160mA
- ◆ Two wire smoke detectors
- ◆ Duct detectors
- ◆ Polling loop devices
- ◆ Key Switch devices

WIRELESS RECEIVER SYSTEMS:

- ◆ 5800 Series
 - 5881L up to 8 zones-50mA
 - 5881M up to 16 zones-50mA
 - 5881H up to 86 zones-50mA
- ◆ All Receivers Support
 - Diversity reception with two antennas
 - Remote mounting for best location
 - Use of second receiver for maximum coverage or tough installations
 - Unique supervision and low battery indications by point

TRANSMITTERS:

- ◆ 5800 Series
 - Three volt Duracell lithium batteries
 - One mile range
 - Tamper standard

AGENCY LISTINGS:

- ◆ UL Residential Fire and Burglary and CFM
- ◆ UL Commercial Burglary when using the VISTA-50PUL

COMMUNICATIONS:

- ◆ Touch tone or pulse
- ◆ Formats supported: ADEMCO Contact ID, ADEMCO 4 + 2 Express, ADEMCO low speed
- ◆ 3+1, 4+1 and 4+2 reporting
- ◆ Reporting capabilities: Split, Dual, Split/Dual
- ◆ Low battery reports 11.2-11.6 VDC
- ◆ Expanded reporting
- ◆ Up to four digit PABX code supported
- ◆ True dial tone detection
- ◆ Double pole line seizure
- ◆ AC loss and restoral reporting supported

Ordering Information:

Part No.	Description
VISTA-50P	Control Panel
VISTA-50PUL	Control Panel UL Commercial