

VISTA-15P

As part of ADEMCO's VISTA PLUS Series of residential controls, the feature-rich VISTA-15P lets you deliver more value to your customers on each and every sale. The panel's robust system capacities, installation advantages and innovative end-user benefits make the VISTA-15P the ideal choice for any application.

FEATURES:

- Six on-board hardwire zones standard
- Expandable to 32 total zones when used with hardwired and/or wireless expansion modules
- Hardwire expansion up to 16 zones
Wireless expansion up to 26 zones
- Wireless Keys can be programmed without using zones
- Eight output devices
 - Relays (Model 4204 Relay Modules, or 4229 Expansion module), and/or
 - X-10 devices (when used with a 4300 transformer)
- Two low current on-board trigger outputs
- 50 Event Log viewable at system keypads with time/date stamp
- 32 system user codes assignable to either partition
- Two installer configurable zone types allows the installer to "create custom zone types" by assigning all zone attributes
- Multiple actions on output devices depending on system "state"
 - Turns light off when system arms
 - Turns same lights on when system disarms
 - Flashes same lights when system is in alarm
- Built-in phone line cut monitor with programmable delay and annunciation options
 - Display on system keypads
 - Trigger local sounders
 - Trigger system bell
- Supports four-wire, and up to 16 two-wire smokes
 - Works with Sentrol CleanMe™ maintenance signal

Valuable End-User Features

- Now viewable on system keypads:
 - Exit countdown
 - Time and date display*
 - Event log*
- Auto keypad backlighting on entry
- Keyswitch arming
- Programmable macro buttons and single button arming
- A variety of wireless remote controls for single button operation
- User scheduling
 - Automatically activates X-10® and relays at programmed times
 - Latchkey reports to pagers
 - Auto arm/disarm
 - "User access" time windows
- Supports up to two numeric pagers
- VIP Module allows system control from any touchtone phone
- Chime by zone

Security Dealer Features

- Automatic System Load Shed
 - During extended AC power fail, the system battery will be disconnected to prevent irreversible battery failure. Reduces service calls to replace batteries
- Dynamic Signaling
 - Reduces redundant reporting to the central station when multiple reporting methods are used; i.e. digital dialer and AlarmNet Radio
- False alarm prevention features help reduce end users triggering false alarms

**Requires custom alpha keypad*



**Control
Panel**

**ADEMCO
GROUP**

VISTA-15P

SPECIFICATIONS:

Electrical

- Aux power 12 VDC, 600mA max
- Seven hour standby at 400 mA aux load with four amp hour battery
- 16.5 VAC/25 VA transformer
- Alarm output 12 VDC, 2.0 amps max
- For UL installations, combined aux and alarm output cannot exceed 700mA

Output Control

- Supports a maximum of eight output devices (combination of relays and/or X-10) plus two onboard triggers

Zones

- Six hardwired zones
- Selectable response: 10msec, 350msec, 750msec
- 16 selectable zone types plus 2 configurable zone types
- Programmable swinger suppression

Expansion Devices

- 4219 - Eight hardwired zones - 16mA
- 4204 - Up to four relays - 15mA standby (each active relay draws an additional 40mA)
- 4229 - Eight hardwired zones and two relays - 36mA (each active relay draws an additional 40mA)

Accessories

- 4286 VIP Voice Module – 220mA
- 5881ENL supports up to eight zones – 60mA, 5881ENM supports up to 16 zones – 50mA, 5881ENH supports up to 26 zones – 50mA
- Supports Eagle 1225 and 1221 boards

Keypads

- 6160 Custom English (required for programming) – 100mA
- 6150 Fixed English LCD 85mA/40mA

Agency Listings

- UL Residential Fire, Burglary and CFM

Smoke Detectors

- Supports up to 16 two-wire smoke detectors
- Supports four-wire smoke detectors

Communications

- Touchtone or pulse
- Formats supported
 - ADEMCO Contact ID
 - ADEMCO 4 + 2 Express
 - ADEMCO low speed
 - SESCOA/Radionics
- 3 + 1, 4 + 1 and 4 + 2 reporting
- Reporting capabilities
 - Split
 - Dual
 - Split/Dual - True dial tone detection
- Low battery reports 11.2 – 11.6 VDC
- AC loss and restoral reporting supported

**Control
Panel**

ORDERING:

Part No.	Description
VISTA-15P	Control Panel

165 Eileen Way, Syosset, NY 11791
Copyright ©2002 Pittway Corporation
ADEMCO is an ISO9001 Registered
Company

**ADEMCO
GROUP**